



Mission Statement

The goal of AMS is to provide the highest quality, best performing products available. By utilizing research and development, and rigorous testing programs AMS will never compromise the quality or performance of our products. In addition, AMS will only provide the finest customer service offering only parts and advice that are in the best interests of the customer. AMS was built on a foundation of integrity. This is who we are; this is what you can count on.

Disclaimer

A vehicle modified by the use of performance parts may not meet the legal requirements for use on public roads. Federal and state laws prohibit the removal, modification, or rendering inoperative of any part or element of design affecting emissions or safety on motor vehicles used for transporting persons or property on public streets or highways. Use or installation of performance parts may adversely affect the drivability and reliability of your vehicle, and may also affect or eliminate your insurance coverage, factory warranty, and/or new OEM part warranty. Performance parts are sold as-is without any warranty of any type. There is no warranty stated or implied due to the stresses placed on your vehicle by performance parts and our inability to monitor their use, tuning, or modification.

Instructions

These instructions are provided as a guide only as there are many variables that cannot be accounted for concerning your particular vehicle. These variables include but are not limited to model/model year differences, the presence of non-OEM parts and modifications that may already be or were previously installed. A basic knowledge of automotive parts and systems is helpful but a better understanding of the parts and systems on your particular vehicle may be required.

If you have any questions or issues at any time during the installation of your AMS product(s) please call us for technical assistance. The AMS tech line can be reached M-F, 9AM-PM Central time at 847-709-0530 for AMS products only.

Instructions:

1. Remove the front bumper and OEM Intercooler.
2. Remove the weight that sits behind the Intercooler as shown below.



3. Remove the grommets from the factory intercooler and install them on the AMS intercooler.



4. Hang the AMS intercooler on the side rubber mounts and bolt the intercooler through the holes it lines up with underneath using the supplied nuts and bolts.



5. Connect the intercooler piping and check for leaks.
6. Re-install bumper and any other parts removed to access the intercooler.

